



BEHR® WATER-BASED STAIN & POLY IN ONE

- Delivers Rich Color and Protection in One Step
- Can Be Used Over Polyurethane Finishes
- Dries in 1 Hour
- Time Saving Application
- Enhances Wood Grain
- Less Odor than Oil-Based Products

No. B6200 Series
No. B6300 Series

Available in a Tint Base and Assorted Pre-tinted Colors



Prep Before Use



2 Coats Required



Spread Rate:
125 Sq. Ft./Qt.



Clean-Up:
Soap & Water

READY TO USE. PROTECT FROM FREEZING.

WHERE TO USE: Properly prepared interior surfaces such as furniture, moldings, cabinets, trim, and wood doors.

Do not use on floors.

CAUTION: Surface may be slippery when wet.

SURFACE PREPARATION* (Proper surface preparation is required)

FOR STRIPPED, UNSTAINED OR RAW WOOD:

- Before starting, surface must be dry, clean and free of dirt, grease and glue.
- Sand the wood in the direction of the grain using fine-grade sandpaper (#150-220 grit) until smooth. Remove all sanding dust.
- To help ensure uniform acceptance of stain color and beautiful results, pretreat new or raw wood with BEHR® Water-Based Pre-Stain Wood Conditioner, following label directions.

FOR PREVIOUSLY FINISHED WOOD THAT IS NOT BEING STRIPPED:

- Before starting, surface must be dry, clean and free of dirt, grease and glue.
- Lightly sand the existing finish with 400 grit sandpaper to ensure adhesion. Remove all sanding dust.

PRODUCT PREPARATION AND COLOR TESTING

- Stir BEHR Stain & Poly In One thoroughly before and occasionally during use. Do not thin.
- Always test Stain & Poly on a scrap piece or hidden area of wood to verify desired color.

APPLICATION

- Using a high quality nylon/polyester bristle brush, dip approximately an inch into the can, gently tapping it against the inside to remove any excess. Apply a very THIN, even coat following the direction of the grain. Make sure to maintain a “wet” edge.
- To minimize the brush marks and bubbles after staining, tip off the surface by holding the brush at a 45 degree angle and lightly run the bristles over the entire length of the wood.

- Let the first coat dry for 1 hour or more. Dry time may be extended due to high humidity, low temperatures, and inadequate ventilation or if the coat is applied too thick.
- Lightly sand the surface between coats with fine sand paper (#400 grit). Remove all dust. Brush on a second thin coat following directions above. To deepen the color, apply a third coat. NOTE: For additional protection, without adding color, add a coat of BEHR Fast Drying Water-Based Polyurethane. Please refer to the back label of the container for application instructions.

DISPOSAL

- For disposal of empty containers and unused product contact your household refuse collection service.

LIMITED WARRANTY

- Visit behr.com/warranty or call 1-800-854-0133 Ext. 2 for more information.

WARNING If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING Cancer and Reproductive Harm –
www.P65Warnings.ca.gov

WARNING! IRRITANT CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CONTAIN: DIPROPYLENE GLYCOL N-PROPYL ETHER, CARBON BLACK, TITANIUM DIOXIDE AND CRYSTALLINE SILICA. Avoid contact with skin and eyes and avoid breathing vapors, spray mist and sanding dust. Sanding, grinding or abrading may release sanding dust, which may be harmful if inhaled and has been shown to cause lung damage or cancer with long term exposure. Do not breathe dusts, vapor, or spray mist. To avoid breathing in dust, vapors, and spray mist, open windows and doors or use other means to ensure fresh air entry during application, drying, sanding, and/or abrading. If properly used, a respirator (NIOSH approved with particulate pre-filter) may offer additional protection and should be used if adequate ventilation cannot be provided; obtain professional advice before using. If you experience eye watering, headaches, or dizziness during application or drying, increase fresh air or leave the area. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.**

PLEASE SEE PRODUCT LABEL FOR SPECIFIC WARNINGS. WARNINGS MAY VARY BETWEEN PRODUCTS AND OR COLORS.



©2021 Behr Process Corporation
Santa Ana, CA 92705 U.S.A. • behr.com
V.O.C. (C.O.V.) <275 g/L • REV. 9/21