



## BEHR® DECKplus® Transparent Waterproofing Wood Finish

- For Decks, Fences & Siding
- 100% Acrylic
- Beautifies Wood
- UV Protection
- Mildew Resistant Finish

No. 400 Clear  
No. 401 Cedar Naturaltone  
No. 402 Redwood



**Must Prep**  
Before Applying  
Wood Finish



**2 Thin Coats**  
Required



**Spread Rate:**  
1<sup>st</sup> Coat 300-350 Sq. Ft./per Gal  
2<sup>nd</sup> Coat 600-700 Sq. Ft./per Gal



**Soap & Water**  
Clean-Up

**CAUTION:** Finished surfaces may become slippery when wet.

### WHERE TO USE

- “For Wood Substrates Only” Recommended for properly prepared new to slightly weathered, unsealed exterior wood surfaces (0-5 years exposure) such as: Decks, Railings, Shakes, Shingles, Siding, Roofs, Fences and Wood Patio Furniture.

### SURFACE PREPARATION† (Proper Surface Preparation is Required.)

- To remove failing coatings or to remove loose fibers use a product such as BEHR PREMIUM® No. 64 Wood Stain & Finish Stripper followed by BEHR PREMIUM No. 63 All-In-One Wood Cleaner to neutralize the wood.
- When stripping is not needed, the surface **MUST** be prepared with a product such as No. 63 Wood Cleaner to remove mill glaze and clean the wood surface.
- After using either No. 64 or No. 63, rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24” away from the surface.
- Allow the area to dry at least 24 hours before coating.
- If needed, lightly sand to remove any wood fibers/fuzz.
- See [behr.com](http://behr.com) for additional product information.

### APPLICATION

- For best results, a pad applicator is recommended over large deck areas.
- Must apply between 40-90° F.
- Avoid applying in direct sunlight or to hot surfaces.
- Do not use if rain is expected within 24 hours.
- The surface must be completely dry before application.
- For multiple gallons, combine into larger container for color uniformity.
- **DO NOT THIN PRODUCT.**
- Stir product occasionally throughout application.
- Test product for penetration and color on a small hidden area before proceeding.
- Use of rollers should be limited to rough surfaces only.
- Use a 3/8” nap roller, nylon/polyester brush, pad applicator or airless sprayer (.015 - .019” tip, 60 mesh filter).
- For airless sprayer, work in small sections lightly saturating the surface and immediately back-brush to eliminate puddling, remove excess and evenly distribute the stain.
- Maintain a wet edge when applying.
- Apply product end to end or to board lengths to prevent lap marks.
- Over application of stain will lead to surface failure including peeling and cracking.

- Two thin coats required.
- For optimum performance, coat all accessible sides.

### DRY TIME

- 1-2 hours before recoat. Allow 72 hours for full cure.
- Additional dry time may be needed in cooler temperatures and higher humidity

### DISPOSAL

- For disposal of empty containers and unused product contact your household refuse collection service.

### LIMITED WARRANTY

- 2 years horizontal surfaces, 4 years vertical surfaces.
- Visit [www.behr.com/warranty](http://www.behr.com/warranty) or call 1-800-854-0133 Ext. 2 for more information.

**†WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

**WARNING!** Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

*A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.*

**⚠ WARNING** Cancer and Reproductive Harm – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.** To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

**CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.**

